

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number: **0 541 194 A2**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number: 92250321.4

(51) Int. Cl.<sup>5</sup>: **F23L 7/00, F23G 5/30,  
F23G 5/16**

(22) Date of filing: 04.11.92

(30) Priority: 05.11.91 JP 288583/91

(43) Date of publication of application:  
12.05.93 Bulletin 93/19

(84) Designated Contracting States:  
**CH DE FR GB IT LI**

(71) Applicant: **MITSUBISHI JUKOGYO KABUSHIKI  
KAISHA**  
5-1, Marunouchi 2-chome Chiyoda-ku  
Tokyo 100(JP)

(72) Inventor: **Okuno, Satoshi, c/o Yokohama  
Dockyard & Mach. Wrks**  
**Mitsubishi Jukogyo K.K., 12, Nishiki-cho  
Naka-ku, Yokohama-shi,  
Kanagawa-ken(JP)**  
Inventor: **Yamamoto, Hirotami, c/o Yokohama  
Dockyard & Mach.**  
**Works, Mitsubishi Jukogyo K.K., 12,  
Nishiki-cho  
Naka-ku, Yokohama-shi,  
Kanagawa-ken(JP)**  
Inventor: **Nishikawa, Susumu, c/o Yokohama  
Res. & Dev. Center**  
**Mitsubishi Jukogyo K.K., 12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**  
Inventor: **Honda, Hiroki, c/o Yokohama Res. &  
Dev. Center**  
**Mitsubishi Jukogyo K.K., 12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**  
Inventor: **Terasawa, Yoshinori, c/o Yokohama  
R&D Center**  
**Mitsubishi Jukogyo K.K., 12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**

(74) Representative: **Meissner, Peter E., Dipl.-Ing.  
et al**  
**Meissner & Meissner, Patentanwaltsbüro,  
Hohenzollerndamm 89  
W-1000 Berlin 33 (DE)**

(54) Method and apparatus for waste incineration.

(57) A method of incinerating wastes while controlling the production of dioxins wherein water vapor or water is sprayed in the main combustion zone of an incinerator. An apparatus for practicing the method of waste incineration, including a line for supplying main combustion air, either alone or together with a line for supplying recycled combustion gas, to the incinerator from below its hearth, is provided with a line for supplying water vapor or water in communication with the line or lines.

EP 0 541 194 A2

# FIELD OF THE INVENTION AND RELATED ART STATEMENT

The present invention relates to a method of incinerating wastes from environmental facilities and products and an apparatus therefor, and more particularly to a method for low-pollution (limited dioxin production) incineration of domestic refuses, industrial wastes, sewage, human wastes, sludges from paper industry, and other wastes such as organic compounds containing chlorine compounds and also to an apparatus therefor.

Detection of highly toxic dioxins in the flue gas, ash residue, flyash, etc. from municipal refuse incinerators is causing a growing concern these days. Investigations on the methods of analysis, the mechanism of evolution, and techniques for control of the dioxins are under way in industrial-academic circles throughout the world. Reports have been made on high-temperature combustion, retention time, etc. aimed at complete incineration. However, the data presented on the subjects are rather meager, and a breakthrough is being sought in vain.

## OBJECTS AND SUMMARY OF THE INVENTION

In view of the state of art described above, the present invention has for its object to provide a low-pollution incineration method and apparatus capable of controlling the production of highly toxic dioxins upon incineration of various wastes including organic wastes that contain chlorine compounds.

The invention realizes the object by providing:

(1) A method of incinerating wastes while controlling the production of dioxins, characterized in that water vapor or water is sprayed in the main combustion zone of an incinerator; and


(2) An apparatus for incinerating wastes having a line for supplying main combustion air, either alone or together with a line for supplying recycled combustion gas, to an incinerator from below the hearth thereof, characterized in that a line for supplying water vapor or water is provided in communication with said line or lines.

The invention has now been arrived at after extensive experimental studies on ways for controlling the secondary production of dioxins and decomposing any such products in consideration of the fact that they are aromatic chlorine compounds. The invention thus provides a method and an apparatus for incineration adopting a system for supplying water vapor or water to the main combustion zone of the incinerator using primary combustion air as the entraining medium.

With regard to the mechanism of formation of dioxins, reports have been made that they easily form during the thermal decomposition process of organic substances and that there are many competing reactions for their production. However, much remain to be clarified and diverse investigations have just got under way at various research institutes and laboratories.

The present inventors were interested in the fact that dioxins are aromatic (cyclic hydrocarbon) chlorine compounds and conceived of either thermally decomposing (i.e., opening) their benzene rings or preventing the formation of the rings. As a consequence, injection of water vapor or water to the main combustion zone has now been adopted. In this way decomposition of dioxins and control of dioxin production can be accomplished concurrently by thermal decomposition and combustion reactions. Thus, low-pollution incineration can be realized.

This mechanism of decomposition and control of dioxins is presumably represented by an overall reaction formula:



## BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic diagram of the first embodiment of the present invention as applied to a fluidized-bed incinerator;

Fig. 2 is a schematic view of the second embodiment of the invention as applied to a stoker-fired incinerator;

Fig. 3 is a schematic view of the third embodiment of the invention as applied to a fluidized-bed incinerator;

Fig. 4 is a schematic view of the fourth embodiment of the invention as applied to a rotary kiln;

Fig. 5 is a vertical sectional view of the fifth embodiment of the invention as applied to a fluidized-bed incinerator;

Fig. 6 is a cross sectional view of the fifth embodiment;

Fig. 7 is a sectional view of a water spray nozzle for use in the present invention;

Fig. 8 is a flow chart of a testing equipment used to confirm the effects of the invention; and

Fig. 9 is a graph showing the relation between the water vapor injection rate and the dioxins concentration.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

As the first embodiment, the present invention as applied to a fluidized-bed incinerator for municipal wastes including organic wastes that contain chlorine compounds will now be described with reference to Fig. 1. In Fig. 1, the numeral 1 designates a waste feeder, 2 a fluidized-bed incinerator, 3 a fluidizing-air fan, 4 a flue gas-circulating blower, 5 a secondary-air fan, 6 an ash cooler, 7 an ash hopper, 8 a heat recoverer, 9 a flue gas fan, 10 a flue gas-treating unit, 11 a stack, and 12 a wind box assembly.

The flue gas-circulating blower 4 and secondary-air fan 5 are driven when necessary.

Water vapor or water is supplied at the points shown in Fig. 1. The construction is such that it can be injected into either (A) a fluidizing-air line or (B) a flue gas-circulating line.

Wastes to be incinerated are fed via the feeder 1 to the fluidized-bed incinerator 2. Fluidizing air (primary air) is ordinary atmospheric air supplied by the fluidizing-air fan 3. Depending on the type of wastes being handled, treated flue gas is supplied as a part of primary air by the flue gas-circulating blower 4 to the wind box assembly 12 to adjust the percentage of excess air and the fluidized state in the fluidized-bed zone. In that case multistage combustion is carried out, effecting controlled combustion (low air excess percentage combustion) in the fluidized-bed zone and combustion in the freeboard with secondary air supplied by the secondary-air fan 5.

The ash residue and other noncombustible matter that collect at the bottom of the furnace are cooled by the ash cooler 6, separated from fluidized sand, and stored in the ash hopper 7. The gas, on the other hand, is conducted through the heat recoverer 8, flue gas fan 9, and flue gas-treating unit 10, and then released from the stack 11 to the atmosphere.

In experiments with the apparatus described above, water vapor or water was sprayed over the fluidizing air to capture dioxins that are produced by the incineration of wastes containing chlorine compounds. It was confirmed that up to 99.1% of the dioxin contents was thus removed.

The amount of water, or water vapor as water, added was, in terms of the molar weight to the carbon amount in the combustibles, 0.88 ( $H_2O/C$  molar ratio). The combustion temperatures were as given in Table

1. The properties of the treated gas, also shown in the table, reflected favorable low-pollution incineration.

T a b l e 1

Experiment Item	With water added in accordance with the invention	Without water addition as usual
Furnace outlet air ratio *	1. 6 8	1. 6 2
Amount of water added (H <sub>2</sub> O mol / C mol)	0. 8 8	0
Temperature inside the fluidized bed	6 7 2 °C	8 9 8 °C
Freeboard temperature	9 3 0 ~ 1 0 0 0 °C	9 5 0 ~ 9 9 0 °C
Retention time at or above 850 °C	ab. 2 sec.	ab. 2 sec.
Furnace outlet gas composition	O <sub>2</sub>	8. 4 9 %
	CO <sub>2</sub>	1 2. 3 7 %
	CO	4 5 p p m
	NO <sub>x</sub>	7 2 p p m
	Dioxins	6 0 ng/Nm <sup>3</sup>
		6 5 0 0 ng/Nm <sup>3</sup>

\* Furnace outlet air ratio =  
 quantity of actually supplied air/theoretical  
 combustion air quantity

In Fig. 2 is shown the second embodiment of the invention as applied to a stoker-fired incinerator.

In the figure, 21 is a feed hopper for introducing waste to be incinerated, 22 is a feeding chute, 23, 24, 25 are a plurality of stoker units arranged stepwise, 26 is a draft line for forcing primary air into the individual stoker units, and 27 is an ash conveyor installed beneath the stoker units.

A spray nozzle 28 is provided in the upper part of the combustion chamber above the stoker and is supplied with water or water vapor by a supply line 29. A line 29a branches off from the line 29 into communication with the draft line 26.

Waste to be incinerated is introduced through the feed hopper 21 and feeding chute 22 into the furnace, burned by the stoker units 23, 24, 25, and discharged in the form of ash. Here water or water vapor as an agent to be injected is forced into the primary air draft line 26 or into the main combustion zone 31 above the stoker.

Fig. 3 illustrates the third embodiment of the present invention as applied to a fluidized-bed incinerator.

As shown, 35 is the main body of the incinerator, 36 a fluidized bed, 37 wind boxes, 38 a freeboard, 39 an inlet for feeding waste to be incinerated, 40 a conduit for introducing water or water vapor, and 42 an inlet pipe for supplying fluidizing air to the lower part of the fluidized bed 36.

The waste to be incinerated, fed through the inlet 39 into the incinerator body 35, is gasified by thermal decomposition in the fluidized bed 36. The resulting gas flows upward through the main combustion zone 43, secondary combustion zone 44, and tertiary combustion zone 45. Secondary air is supplied to the main and secondary combustion zones 43, 44, and tertiary air is supplied between the second and tertiary combustion zones 44, 45.

When water or water vapor is used, it is introduced into the main combustion zone 43 where apparently benzenes and phenols as precursors of dioxins are being produced.

Fig. 4 shows the fourth embodiment of the invention as applied to a rotary kiln.

In the figure, 50 is a rotary kiln, 51 a waste feeder, 52 a gas recombustion chamber, and 53 an after-burning stoker provided in the lower part of the recombustion chamber 52. In the recombustion chamber 52, combustion gas from a main combustion zone 54 is discharged by way of a secondary combustion zone 55. Numeral 56 indicates a line through which secondary air is supplied. Spray nozzles 57, 58 for introducing water or water vapor are mounted in end walls of the rotary kiln 50 and recombustion chamber 52, respectively.

Waste to be incinerated is fed by the feeder 51 to the rotary kiln 50. Inside the kiln 50, the waste is thermally decomposed into a gaseous form by the radiant heat from the recombustion chamber 52 at a high temperature, and then is secondarily burned in that chamber. Water or water vapor as an injection agent is either forced by the nozzle 57 directly into the decomposing-gasifying zone of the rotary kiln 50 where the precursors of dioxins are easily formed or introduced by the nozzle 58 into the main combustion zone 54.

Figs. 5 and 6 show the fifth embodiment of the invention as applied to a fluidized-bed incinerator, intended to clarify a typical arrangement of water spray nozzles.

Referring to the figures, 62 is the main body of the fluidized-bed furnace, 63 a fluidized bed, 64 wind boxes, 65 a freeboard, 66 a waste hopper, 67 an ash residue outlet, 68 a plurality of water spray nozzles mounted in the surrounding wall of the fluidized-bed incinerator body 62, and 69 a plurality of secondary air nozzles likewise mounted in the surrounding wall. The water spray nozzles 68 and secondary air nozzles 69 are located with inclination at predetermined angles to the axial center of the incinerator (in a pattern represented by alternate long-and-short-dashes lines in Fig. 6) so as to produce a swirl flow in the furnace and achieve an enhanced gas-water mixing and stirring effects.

Fig. 7 illustrates the construction of an embodiment of the water or water vapor spray nozzle for use in the present invention. This spray nozzle is of a type which can maintain water supply to the spray tip at the front end constant by keeping a constant water supply pressure and adjusting the return water pressure (water quantity), and hence can maintain the size of sprayed water droplets constant regardless of the flow rate. In the figure, 69 is the main body of the spray nozzle, 70 a protective sleeve, 71 an inlet pipe for introducing spray water, 72 a return pipe, and 73 a refractory wall of the furnace body. The quantity of spray issuing from the nozzle is increased or decreased by adjusting the opening of a flow regulating valve (not shown) installed downstream of the return pipe 72. In the practice of the invention water or water vapor is constantly injected at a controlled rate.

Fig. 8 is a flow chart of a testing equipment used to confirm the advantageous effects of the present invention. First, waste to be burned is fed to a cylindrical fluidized-bed incinerator 81 via a metering hopper 82 and a feeder 83. The combustion gas leaving the top of the furnace is cooled as it passes through two indirect air-cooled gas coolers 85, 86 in tandem. After dust removal by a bag filter 87, the cleaned gas is discharged by an induced draft fan 89 to the atmosphere via a stack 90.

Meanwhile, water vapor is used as an injection agent and is injected at a predetermined rate into primary air which is boosted in pressure by a forced draft fan 91 and heated to a given temperature by an air heater 92. For the purposes of the experiments the amounts of dioxins produced were measured at the inlet of the bag filter 87. The symbol 81a indicates a (propane) gas burner and G, a gas sampling point.

With the testing equipment described above, experiments were made on ordinary combustion without the injection of water vapor and on combustion at varied rates of water vapor injection. Resulting concentrations of dioxins (PCDDs + PCDFs) are graphically represented in Fig. 9. As for the combustion

conditions used, the fluidized-bed temperature was 700 °C and the O<sub>2</sub> concentration in the combustion gas was 7%.


The water vapor injection rate was varied over the range of 0.1 to 0.46 kg H<sub>2</sub>O/kg waste (H<sub>2</sub>O/C molar ratio = 0.2 to 0.88). The graph shows that the presence of only a small amount of water vapor reduced the overall dioxin concentration sharply, to less than one-twentieth of the concentration when no such vapor was injected. The largest injection reduced the concentration to nearly one-hundredth; indicating the amazing effect of the invention.

For the injection of water or water vapor in conformity with the invention it is only necessary to keep the injecting point at a temperature of 700 °C or upwards, decide an injection rate according to the desired dioxin reduction ratio, and inject the water or water vapor constantly at a controlled rate corresponding to the rate of incineration.

As described above, the present invention renders it possible to control or reduce markedly the secondary production of dioxins during the incineration of wastes containing chlorine compounds that is causing a global concern today. The invention thus realizes low-pollution incineration and its contribution to the protection of earth environments is unmeasurably great.

#### Claims

1. A method of incinerating wastes while controlling the production of dioxins, characterized in that water vapor or water is sprayed in the main combustion zone of an incinerator.
2. An apparatus for incinerating wastes having a line for supplying main combustion air, either alone or together with a line for supplying recycled combustion gas, to an incinerator from below the hearth thereof, characterized in that a line for supplying water vapor or water is provided in communication with said line or lines.
3. A fluidized-bed incinerator characterized in that a line for supplying water vapor or water is provided in communication with a line for supplying air or recycled combustion gas to the incinerator from below the hearth thereof.
4. A stoker-fired incinerator including air supply lines for supplying combustion air to the lower parts of individual stoker units, characterized in that a line for supplying water vapor or water is provided in communication with said air supply lines.
5. A rotary kiln including a gas recombustion chamber, characterized in that lines for supplying water vapor or water are provided in communication with the inlet and the gas recombustion chamber of said kiln.
6. The fluidized-bed incinerator as claimed in claim 3, characterized in that a line for supplying water vapor or water is provided in the upper part of the main combustion zone of said incinerator.
7. The stoker-fired incinerator as claimed in claim 4, characterized in that a line for supplying water vapor or water is provided in the upper part of the main combustion zone of said incinerator.
8. The rotary kiln as claimed in claim 5, characterized in that a line for supplying water vapor or water is provided in the upper part of the main combustion zone of said incinerator.
9. An incinerator for wastes characterized by a plurality of nozzles for introducing water vapor or water into the incinerator, said nozzles being arranged at predetermined angles to one another so as to produce a swirl flow of the water vapor or water inside.





2-6-4




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9





(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number:

**0 541 194 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(21) Application number: 92250321.4

(51) Int. Cl.<sup>5</sup>: **F23L 7/00, F23G 5/30,  
F23G 5/16, F23G 5/00**

(22) Date of filing: 04.11.92

(30) Priority: 05.11.91 JP 288583/91


(43) Date of publication of application:  
12.05.93 Bulletin 93/19(84) Designated Contracting States:  
**CH DE FR GB IT LI**(88) Date of deferred publication of the search report:  
27.10.93 Bulletin 93/43(71) Applicant: **mitsubishi JUKOGYO KABUSHIKI  
KAISHA**  
5-1, Marunouchi 2-chome  
Chiyoda-ku  
Tokyo 100(JP)(72) Inventor: **Okuno, Satoshi, c/o Yokohama  
Dockyard & Mach. Wrks  
Mitsubishi Jukogyo K.K.,  
12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ken(JP)**  
Inventor: **Yamamoto, Hirokami, c/o Yokohama  
Dockyard & Mach.  
Works,**

**Mitsubishi Jukogyo K.K.,  
12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ken(JP)**  
Inventor: **Nishikawa, Susumu, c/o Yokohama  
Res. & Dev. Center  
Mitsubishi Jukogyo K.K.,  
12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**  
Inventor: **Honda, Hiroki, c/o Yokohama Res. &  
Dev. Center  
Mitsubishi Jukogyo K.K.,  
12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**  
Inventor: **Terasawa, Yoshinori, c/o Yokohama  
R&D Center  
Mitsubishi Jukogyo K.K.,  
12, Nishiki-cho  
Naka-ku, Yokohama-shi, Kanagawa-ku(JP)**

(74) Representative: **Meissner, Peter E., Dipl.-Ing.  
et al  
Meissner & Meissner,  
Patentanwaltsbüro,  
Postfach 330130  
D-14171 Berlin (DE)**(54) **Method and apparatus for waste incineration.**

(57) A method of incinerating wastes while controlling the production of dioxins wherein water vapor or water is sprayed in the main combustion zone of an incinerator (2). An apparatus for practising the method including a line for supplying main combustion air by fan (3), either alone or together with a line for supplying recycled combustion gas from blower (4), to the incinerator wind box (12) below its hearth, is provided with a line for supplying water vapor or water in communication with either (A) the fluidizing air line or (B) the flue gas recirculation line.

FIG. 1



EP 0 541 194 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number

EP 92 25 0321

## DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X A	US-A-4 960 057 (OHSHITA ET AL) * column 2, line 1 - line 13; figure 1 * ---	1 3,6	F23L7/00 F23G5/30 F23G5/16 F23G5/00
X	DE-A-2 533 010 (COMMONWELTH SCIENTIFIC AND INDUSTRIAL RESEARCH ORGANISATION) * page 6, line 13 - page 7, line 6 * * page 8, line 24 - line 29; figure 1 * ---	2,3	
X	US-A-5 038 690 (KUMAGAI ET AL) * column 1, line 51 - line 65 * * column 3, line 35 - column 4, line 26 * * figure 1 * ---	1-3	
A	DE-A-3 125 429 (ERK ECKROHRKESSEL) * page 4, line 3 - line 31; figures 1-3 * ---	1,9	
A	FR-A-2 316 542 (VON ROLL) * page 4, line 2 - page 5, line 32 * * figure 1 * ---	4,7	
A	US-A-4 658 736 (WALTER) * column 2, line 33 - column 3, line 31; figure 1 * ---	5,8	TECHNICAL FIELDS SEARCHED (Int. Cl.5)
A	EP-A-0 235 531 (ISHIKAWAJIMA-HARIMA HEAVY INDUSTRIES CO) -----		F23L F23G
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 03 SEPTEMBER 1993	Examiner VRUGT S.C.
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document  T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P0601)